



Oil Cleaning Filter System
to enhance plant productivity.

Customer Service Die Casting.

Maintaining hydraulic fluid for optimum performance.

Particularly suitable for die-casting applications with high volume flows, our Oil Cleaning Filter System can reduce hydraulic system breakdowns by up to 60 %.

With a filter fineness of 3 µm, the system maintains water glycol 24/7, reducing wear on pumps, valve, and hydraulic components – ensuring better productivity, less scrap and delivering higher uptime for the die-casting cell.

Longer change intervals of the fluid lead to lower service and maintenance costs. Less friction in the system results in lower energy consumption.

Benefits for your foundry

- **Higher profitability** – Lower service and maintenance costs (longer lifetime of hydraulic components, hydraulic liquid, and system filter)
- **Increased productivity** – Reduction of unscheduled downtime
- **Increased energy efficiency** – Lower energy consumption based on less friction in the system



Technical data.

		Oil Cleaner 2000	Oil Cleaner 4000
Fluid quantity		To 2000 liter	From 2000 liter
Dirt holding	kg	2	4
Pump capacity	l/h	260	780
Power consumption, approx.	kW	0.18	0.37
Base	mm	500 × 700	500 × 700
Height	mm	810	1095



System downtime.

- The Oil Cleaner Filter System is installed on site
- The downtime is ½–1 day (depending on tank capacity)
- We also recommend tank cleaning as part of the installation

Assembly.

- The assembly can be carried out by customer personnel, with the instructions provided
- Alternatively, Bühler can provide a service technician (at extra charge)

Warranty.

24 months, starting from delivery.

Bühler Alzenau GmbH

Business Area Die Casting
Siemensstr. 88, D-63755 Alzenau
www.buhlergroup.com/die-casting
dc.spares@buhlergroup.com

T +49 6023 9194 544
F +49 6023 9194 544

